olivetti





d-COPIA 1600 and 2000

DIGITAL COPIERS

The **Olivetti d-Copia1600** and **d-Copia2000** monochrome A3 digital copiers, with printing option, are an excellent solution for small/medium offices where productivity, reliability and cost-effectiveness are

primary considerations.

They work at speeds of, 16 and 20 ppm, respectively, in A4 format and 8 and 10 ppm, respectively, in A3 format.

An optional GDI interface permits printing from any Windows PC.

Both models have a 350-sheets paper input capacity, larger than competitor models, which can be increased with three optional trays to a top capacity of 1,250 cut sheets.

TWO OF THE MOST COMPACT COPIERS IN THEIR CLASS

UP TO 160 MB OF MEMORY

FIRST COPY OUT IN 5.9 SECONDS

OPERATOR PANEL WITH MONO-FUNCTION KEYS

PRINTING FROM ANY PC IN THE WINDOWS ENVIRONMENT (OPTIONAL GDI INTERFACE)

DUPLEX UNIT FOR TWO-SIDE PRINTING (OPTIONAL)

DUPLEX DOCUMENT FEED (OPTIONAL)



Easy-to-use **OPERATOR PANEL** for quick access to all digital functions



THREE OPTIONAL PAPER TRAYS for maximum supply of 1,250 sheets



Long-life **TONER CARTRIDGE** (up to 15,000 A4 pages with 6% coverage)

TECHNICAL SPECIFICATIONS

	Type desktop/console	Desktop	Power	220-240 VAC, 50/60 Hz
	Technology	Monocomponent, Single laser	100001	220-240 VAC, 30/00 Hz
GENERAL		1 . 3	Absorption	Maximum: 1100W
	Resolution	600 x 600 dpi		Copy/Print: 461 W
	Pages per minute	16/20 cpm		Ready: 104 W Low absorption: 43 W
	Engine speed	d-Copia 1600: 16/8 ppm A4/A3 d-Copia 2000: 20/10 ppm A4/A3		Sleep-Mode: 3,8 W
	Greyscale	256 gradations	Dimensions (WxDxH)	574 x 552 x 502 mm
	Warm-up time	< 20 sec	Weight	40,7 Kg
COPIER	Scanning system	Flat bed scanning by CCD image sensor	Copy weights	Trays: 64-105 g/m² Bypass: 45-160 g/m²
	Printing method	Semiconductor laser and electrographic	Paper capacity (80g)	Tray: 1 x 300 sheets
	First copy time	< 5,9 sec		Bypass: 50 sheets
	Continuous copy	up to 999		Up to 3 optional 300-sheet trays (PF-410)
	Memory	32 MB (Max 160 MB-additional socket:16/32/64/128 MB)		
	Original Size	Books, sheets, 3-D objects max A3	Paper output	Max 250 sheets
	Copy formats	Trays: A3-A5R, Folio, Statement, Letter, Legal, Ledger, Oficio2; Bypass: A3-A6R, Folio, Statement, Letter, Legal, Ledger, Oficio2, Envelopes;	Zoom	25%-400% (steep 1%)
			Immage density regulation	Manual/automatic
OPTIONAL PRINTER	Print System X		Interfaces	USB 2.0 (High-speed)
	Speed A4	16/20 ppm	Emulations	GDI
	CPU	ARM 946-S 150 MHz, FlexRISC	Compatibility	Windows 98 SE, Me, 2000, XP
	Memory	32 MB	Network interface external box (IB-110)	Fast Ethernet 10\100 TX
	Resolution	600x600 dpi		
PAPER OPTIONS	Duplex document - 49 processor Cap (DP-410A) Dim	Paper size: A3-A5R, Folio Paper weight: - 45-160 g/m² (ADF-mode) - 50-120 g/m² (RADF-mode) Capacity: 50 sheets	Paper feeder (PF-410A)	Paper format: A3-A5R, Folio Capacity: 300 sheets Paper weight: 60-105 g/m² Dimensions (WxDxH): 570 x 538 x 135 mm Weight: 7 Kg
		Dimensions (WxDxH): 552 x 483 x 120 mm Weight: 6 Kg	Duplex unit (DU-410)	Format: A3-A5R, Folio Paper weight: 60-80 g/m²
			Platen Cover	
			Cabinet (CP 16H e CP 16L)	

Product performances are referred to an appropriate use under optimal conditions. With the right to change technical specifications. The registrered trademarks are the property of their respective owners. d-Copia 1600 and d-Copia 2000 are distributed by Olivetti S.p.A. (03/06) - Codice: 25403

OLIVETTI UK LIMITED 500 AVEBURY BOULEVARD MILTON KEYNES, MK9 2BE www.olivetti.com



